

Elcometer 108 Hydraulic Adhesion Tester

The Elcometer 108 Hydraulic Adhesion Tester is an extremely versatile Type III adhesion gauge which can be used for many adhesion requirements. Tests can be made on flat or curved (concave and convex) surfaces.

The Elcometer 108 is the ideal gauge for coatings on Tanks, Pipelines, etc.

- Hand-Powered and portable
- Ideal for site work
- · Reusable stainless steel dollies

Elcometer Digital Adhesion Gauge features:

- · Maximum hold displays the highest value reached
- Backlit display for dark areas
- Rubber protective casing
- Switchable Metric/Imperial

The Elcometer 108 can be used with convex and concave dollies, making this the gauge for adhesion of coatings on all pipelines including those with small diameter, tanks and other curved surfaces. There is a wide range of curved dollies available, each designed for a specific range of curvature.







STANDARDS:

ASTM D 4541, ISO 16276-1, NF T30-606

| Technical Sp | ecification | | |
|------------------------------|------------------|---|-------------|
| Part Number | | Description | Certificate |
| UK 240V/EUR 22 | 0V US 110V | | |
| F1081D | F1081C | Elcometer 108/1 Hydraulic Adhesion Tester - Analogue Dial Gauge | 0 |
| F1082D | F1082C | Elcometer 108/2 Hydraulic Adhesion Tester - Digital Gauge | 0 |
| Operating Range | | Analogue: 0 - 18MPa (0 - 2600psi) Digital: 0 - 25MPa (0 - 3600psi) | |
| Analogue Instrument Accuracy | | ±1MPa Metric Scale; 150psi (Imperial Scale) | |
| Digital Instrument Accuracy | | ±3% or 60psi (whichever is the greater) | |
| Dolly Size | Outside Diameter | 19.4mm (0.76") | |
| | Inside Diameter | 3.7mm (0.15") | |
| | Area | 284mm² (0.44sq.inch) | |
| Packing List | | Elcometer 108, ABS carry case, 5 flat dollies, 5 nylon plugs, MC1500 quick curing adhesive, dolly cleaning tool, 2 x LR6 (AA batteries) (Digital gauge only) and operating instructions | |



Elcometer 108 Hydraulic Adhesion Tester

| Accessories | | |
|-------------|---|--|
| T99911135 | Cyanoacrylate Adhesive | |
| T1089646- | Standard Flat Dolly 19.4mm (0.76") | |
| T99923147 | Dolly Cleaning Heating Tongs - EUR 220V / UK 240V | |
| T99923103 | Dolly Cleaning Heating Tongs - US 110V (No Plug) | |

Concave & Convex dollies are available upon request